Prescription Text



2017-11-30

Type

Baselift 6210 - 179 cm

Brand: Granberg

Properties

Lift unit 109.0 - 180.0 cm width 1 motor 2 mid-sides Safety switch



Specifications

Installation

Floor

Height adjustment

Motor-driven, continuously adjustable 30.0 cm (65.0 - 95.0 cm excl. worktop)

Speed level

1.8 cm / sec.

Operation

Built-in button or radio control

Safety

A security strip is located below the worktop's front edge. Contact with the strip stops the lift

Electrical connection

Mains plug for 230 V, max 2.5A

Plumbing connections

Connection is by means of flexible hoses

Lifting force

150 kg

IP-class

IP 20

Frame depth

56.0 - 58.0 cm from wall

Front height

11.8 - 12.5 cm

Dimensions cover plates

Width = Lift's width, Height 43.8 cm, Thickness 1.2-1.6 cm

Depth worktop

58.5 - 63.5 cm

Width

109.0 - 180.0 cm

Space to wall / adjoining cabinet

0.5 cm

Space to wall (for tiles)

1.5 cm

Tiling

From 65.0 cm above floor (alternatively right down to floor)

Delivery modules

Assembled work surface incl. safety switch. Floor mounted motors.

Fittings supplied

Attachments for fronts

Material

Frame and motors in aluminium. Powder coated sheet-metal parts (Alugrey RAL 9006)

Warranty

2 year

